

# 12PR320

12" - 300 W - 97 dB - 8 Ohm



## NOMINAL SPECIFICATIONS

Nominal Diameter	300 mm (12 in)
Overall Diameter	316 mm (12.44 in)
Bolt Circle Diameter	298.5 mm (11.75 in)
Baffle Cutout Diameter	282 mm (11.10 in)
Depth	120 mm (4.72 in)
Flange and Gasket Thickness	12 mm (0.47 in)
<b>Net Weight</b>	<b>2.75 Kg (6.1 lb)</b>
Shipping Box (Single Carton Box)	350 x 346 x 190 mm (13.8 x 13.6 x 7.5 in)
Shipping Weight	3.4 Kg (7.5 lb)

## PART NUMBER

Push Terminals - 8 Ohm Version TBA

## NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4)  $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

## TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	6.4 Ohm
AES Power Handling (1)	300 W
<b>Maximum Power Handling (2)</b>	<b>600 W</b>
<b>Sensitivity (1W/1m)</b>	<b>97 dB</b>
Frequency Range	45-5000 Hz
<b>Voice Coil Diameter</b>	<b>65 mm (2.56 in)</b>
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	17.4 mm (0.69 in)
<b>Magnetic Gap Depth</b>	<b>8 mm (0.31 in)</b>
Flux Density	1.2 T
Magnet	Neodymium Slug
Basket Material	Aluminum
Demodulation	No
Cone Surround (3)	Triple Roll
NET Air Volume filled by Loudspeaker	1.9 dm <sup>3</sup> (0.067 ft <sup>3</sup> )
Spider Profile	1x variable height waves

## THIELE & SMALL PARAMETERS

Fs	42 Hz
Re	5.3 Ohm
Qes	0.39
Qms	7.8
Qts	0.37
Vas	94.8 dm <sup>3</sup> (3.35 ft <sup>3</sup> )
Sd	489 cm <sup>2</sup> (75.80 in <sup>2</sup> )
Xmax (4)	7.37 mm
Xdamage (5)	17 mm
Mms	51.4 g
Bl	13.5 N/A
Le	0.67 mH
Mmd	39.3 g
Cms	0.28 mm/N
Rms	1.74 Kg/s
Eta Zero	1.73 %
EBP	108 Hz

